

DC & ADCooler

Dry-Cooler & Adiabatic Dry-Cooler
for Plastic Industry Dedicated Cooling



DCooler
Cooling capacity
63 ~ 920 kW

ADCooler
Cooling capacity
82 ~ 1.220 kW

Find out more



Eurochiller DCooler & ADCooler range

Boosted Cooling Power with Smart Water Management

Our **DCoolers** deliver high-performance heat rejection using ambient air, offering a sustainable and low-maintenance solution for industrial and commercial cooling systems. Designed for reliability and energy efficiency, they are ideal for applications where water conservation and operational simplicity are key. With robust construction and quiet operation, our dry coolers ensure optimal thermal performance even in demanding environments.

Our Adiabatic version **ADCooler** combines the efficiency of air-cooled systems with the enhanced performance of evaporative cooling. By pre-cooling the incoming air with a controlled water mist, it significantly improves heat rejection during peak temperatures—without the high-water consumption of traditional cooling towers. Perfect for regions with hot climates or high thermal loads, it offers a smart balance between performance, sustainability, and cost-efficiency.



Water-Saving Technology

- **Water-Free Operation:** No need for continuous water supply or treatment. It uses water only when needed, with smart control.
- **Eco-Conscious Design:** Anti-Legionella design with automatic water flushing system.
- **Eco-Friendly Solution:** Ideal for regions with water restrictions or sustainability goals.
- **Minimal Environmental Impact:** No chemical discharge, no water waste, and no risk of legionella.



Energy Efficiency

- **Enhanced Cooling Capacity:** Up to 40% more efficient during peak heat.
- **Low Carbon Footprint:** Energy-efficient EC fans and smart controls reduce electricity usage.
- **Optimized Water Use:** Uses water only during peak conditions, reducing overall consumption.
- **Energy Savings:** Improved thermal efficiency lowers energy demand and operating costs.




Key Benefits

- **Quiet Performance:** Low-noise fans for silent operation in sensitive environments.
- **Long-Term Sustainability:** Durable materials and low maintenance extend product life.
- **Low Maintenance:** No risk of scaling, corrosion, or biological growth. Corrosion-resistant coil materials (copper/aluminum or stainless steel).
- **Compact & Modular Design:** Easy to install and scale according to system needs.

WATER SAVING



ADIABATIC SYSTEM



V-SHAPED COILS



Eurochiller DCooler & ADCooler range

Cutting-Edge Technology and Premium Components

Robust frame structure

Epoxy coating protection

EC Axial fans option

Brushless fans for -20°C installations

Cu-Al Coils

High efficiency thermal exchange

Optional internal water pump

Internal pump with pressurized water circuit



Adiabatic pads

The smart choice against cooling towers

Drainage

Patented system to avoid Legionella issues

Adiabatic solenoid valves

Smart management of pads watering

Ambient friendly

Powerful but eco-friendly

Ready for Industry 5.0



The optional **Chiller Gateway interface** enables seamless integration with the most widely used industrial communication protocols, including Ethernet and Profibus. This feature supports the digital transformation of manufacturing environments by ensuring full connectivity within modern factory.



Dry & Adiabatic - Cooler for Plastic Industry dedicated cooling

Technical Data													
DCooler Version 50Hz		DC-S 60	DC-S 120	DC-S 200	DC-S 270	DC-S 350	DC-S 450	DC-L 250	DC-L 400	DC-L 500	DC-L 600	DC-L 720	DC-L 880
Cooling Capacity (1)	kW	63	125	210	283	363	447	265	378	525	647	752	920
ADCooler Version 50 Hz		ADC-S 80	ADC-S 170	ADC-S 280	ADC-S 380	ADC-S 490	ADC-S 600	ADC-L 350	ADC-L 500	ADC-L 700	ADC-L 850	ADC-L 1000	ADC-L 1200
Cooling Capacity (2)	kW	82	169	282	383	505	630	346	498	694	856	994	1.220
Nominal Water Flow	m3/h	10,8	21,5	36,1	48,7	62,4	80,5	45,6	65,0	90,3	11,3	129,3	158,2
Number of Fans		1	2	3	4	5	6	4	6	8	10	12	14
Power of Fans	kW	2,25	4,5	6,75	9,0	11,25	13,5	8,8	13,2	17,6	22,0	26,4	30,8
IN/OUT Water Connections	[inch]	2"	2 1/2"	3"	3"	3"	3"	4"	4"	4"	4"	4"	4"
Water Content	lt	40	70	140	300	380	460	175	290	410	550	720	790
Length	[mm]	1.770	2.970	4.170	5.370	6.520	7.770	3.970	5.205	6.435	8.380	9.900	10.930
Width * (AD)	[mm]	1.610 (1.910)	1.610 (1.910)	1.610 (1.910)	1.610 (1.910)	1.610 (1.910)	1.610 (1.910)	2.380 (2.680)	2.380 (2.680)	2.380 (2.680)	2.380 (2.680)	2.380 (2.680)	2.380 (2.680)
Height	[mm]	2.145	2.145	2.145	2.145	2.145	2.145	2.600	2.600	2.600	2.600	2.600	2.600
Pump Kit Version	kW	2,3	3,0	5,5	7,5	9,2	11,0	Option not available					

(1) Reference condition: Ambient Air 30°C / Water in/out +40/35°C, 0% Glycol.

(2) According to ENV 1048 regulations without adiabatic pads.

Applications of DCooler & ADCooler in the Plastics Industry

- Plastic Molding Machines
- Chill Rolls
- Shredder Recycling
- Wrap Recycling
- Bag, Bottle, and Film Production

- Injection Molding
- Blown Film Molding
- Stretch Blow Molding
- Profile Extrusion

Eurochiller S.r.l.

Headquarter and production facilities
Via Milano, 69 – 27030 Castello d'Agogna (PV) – Italy
Tel. +39 0384.298985
Service +39 0384.298981
VAT Number IT01482170188



Part of Atlas Copco Group