

EVVS

Air-Cooled Water Chillers
for Plastic Industry centralized cooling

**EURO
CHILLER**
■ Part of Atlas Copco Group



175 ~ 830 kW
Cooling capacity

R454B
Low-GWP Refrigerant

Find out more



New Eurochiller EVVS range

Cutting-Edge Technology and Premium Components

Discover the innovative **EVVS** chillers, utilizing **R454B** refrigerant to significantly minimize environmental impact with a low Global Warming Potential (GWP). EVVS Water Chillers play a vital role in the plastics industry by providing precise temperature control. These units are essential for directly cooling plastics during processing, ensuring that manufacturing machines operate efficiently. By preventing defects, warping, and shrinkage, our cooling solutions guarantee high-quality, dimensionally accurate products. Additionally, they help reduce energy waste and costs. EVVS Water Chillers also enhance safety, extend equipment lifespan, and increase process flexibility, making them indispensable for plastics processing.



Low-GWP Refrigerant

We prioritize environmental sustainability and offer the option to equip your **EVVS** with **R454B** refrigerant, a low global warming potential solution. This low-impact refrigerant helps to reduce greenhouse gas emissions, promoting a greener future.

R454B: GWP = 467



Advanced Multi-Scroll Compressors

At the heart of EVVS there is an **advanced multi-scroll compression system** designed for stable and reliable performance. This technology increases efficiency, reduces vibrations, and extends the lifespan and reliability of the chiller.

HIGH PERFORMANCE



Exceptional Energy Efficiency

EVVS ensures efficient cooling for industrial operations while minimizing energy consumption, thanks to its high **Seasonal Energy Performance Ratio (SEPR HT)**. This reduces operational costs and supports environmental sustainability without compromising performance.

SEPR (HT)* up to 6,40

Energy saving example

EVVS 310 AG HT **SEPR HT = 6,29**

Other conventional Chiller **SEPR HT = 5,45**

EVVS Energy saving / year = 23.127 kW/h

Electricity cost = 0,20 €/kWh

EVVS Energy saving / year = > 4.600,00 €

*Seasonal Efficiency Performance Ratio for Process HT Chillers (EU Reg. 2281/2016) can be used for comparison with other chillers with standard efficiency level.

eurochiller.com

New Eurochiller EVVS range

Cutting-Edge Technology and Premium Components

Robust frame structure

Epoxy coating protection

EC Axial fans

Brushless energy-saving motor

Microchannel coils

Less refrigerant charge / More efficiency

Centrifugal water pump

High pressure and stand-by options



IQ21 PLC controller

Industrial Touch screen display interface

Hydronic configuration flexibility

Brazed plate or Shell & tube evaporator

Scroll compressors - IDVs technology

Optimized for low-GWP refrigerant

Electronic expansion valve

Partial load control optimized

Ready for Industry 5.0



The optional **Chiller Gateway interface** enables seamless integration with the most widely used industrial communication protocols, including Ethernet and Profibus. This feature supports the digital transformation of manufacturing environments by ensuring full connectivity within modern factory.



Air-Cooled Water Chillers for Plastic Industry centralized cooling

Technical Data

EVVS AG R454B HT 50 Hz		175	195	210	245	260	310	350	380	420	480	530	600	660	710	750	830
Cooling Capacity ¹	[kW]	174,6	191,7	208,4	240,4	264,5	315,2	339,3	385,9	420,8	491,4	555,4	592,3	630,0	691,4	729,1	820,4
Power consumption ¹	[kW]	36,6	41,7	47,0	58,4	51,5	61,2	68,8	81,4	93,6	101,1	112,1	126,1	140,2	141,6	155,3	174,0
EER ¹	-	4,77	4,60	4,44	4,12	5,14	5,15	4,93	4,74	4,50	4,86	4,96	4,70	4,49	4,88	4,69	4,71
SEPR HT ² Reg. EU 2281/2016	-	6,62	6,49	6,26	6,10	6,16	6,29	6,08	5,99	5,87	5,98	6,14	5,83	5,72	6,10	5,92	6,03
Compressors / Circuits	-	2 / 1	2 / 1	2 / 1	3 / 1	5 / 2	6 / 2	4 / 2	4 / 2	4 / 2	4 / 2	4 / 2	5 / 2	6 / 2	5 / 2	6 / 2	6 / 2
Number of fans	-	2	2	2	2	3	4	4	4	4	5	6	6	6	7	7	8
Hydronic configurations	-	Single or twin (stand-by) pump option, from 2 to 6 bar Integrated buffer tank option															
IN/OUT water connections	[inch]	3"	3"	3"	3"	4"	4"	4"	4"	4"	5"	5"	5"	5"	6"	6"	6"
Length	[mm]	2.660				3.500				5.020				6.475			
Width	[mm]	1.590				2.230				2.230				2.230			
Height	[mm]	2.520				2.520				2.520				2.520			

(1) Reference condition: Ambient Air 25°C, Evaporator in 20°C / out 15°C, 0% Glycol.

(2) Data declared in compliance with the European Regulation (EU) 2016/2281 regarding Eco-Design requirements for cooling products and high temperature process chillers. Values refer to configuration without pump.

Applications of EVVS Chillers in the Plastics Industry

- Plastic Molding Machines
- Chill Rolls
- Shredder Recycling
- Wrap Recycling
- Bag, Bottle, and Film Production
- Injection Molding
- Blown Film Molding
- Stretch Blow Molding
- Plastic Welding
- Profile Extrusion

Eurochiller S.r.l.

Headquarter and production facilities
Via Milano, 69 – 27030 Castello d'Agogna (PV) – Italy
Tel. +39 0384.298985
Service +39 0384.298981
VAT Number IT01482170188



